

# MASK6T-BL

6.5" design two-way loudspeaker,  
black



The MASK6T is a 6.5" two-way low impedance or 100 volt loudspeaker with timeless design. This cabinet loudspeaker offers incredible intelligibility what makes it ideal for background music and paging purposes. MASK6T loudspeakers are suitable for both indoor and outdoor use as they have an IP64 rating.

MASK6T can be used in 16 ohms (up to 4 loudspeakers in parallel on a standard 4 ohms amplifier channel) or 100 volts. It comes with a high quality 100 volts transformer with several power tapings (60 – 30 – 15 – 6 watts) which can be selected via the rotary switch at the back of the loudspeaker.

The cabinet of MASK6T is made of high quality enforced PP4 ABS and the grille is made of aluminium. The internal bracketing and the shape of the cabinet avoid internal interference and optimise the sound quality of the MASK6T loudspeaker. The loudspeaker has a coated 6,5" paper cone woofer and a 1" silk dome tweeter.

Its phase alignment and wide frequency range makes sure every note, starting from the robust bass over the clean middle range to the crystal clear highs, reaches your ears with an astonishing clarity.

The built-in Auto-Reset 3-step Protection Guard together with the quality components makes MASK6T a fail-safe loudspeaker, even at high power loads!

Thanks to the Intelli-Mount bracket, the MASK6T is easy and fast to install. The Vari-throat horn for the tweeter and the 5° down tilt angle in which the woofer and tweeter are mounted in the cabinet, guarantee a perfect sound dispersion, without the need of a big tilt angle of the cabinet itself. The MASK6T cabinet has a M12 thread mounting point tapped at the back of the cabinet. This way a lot of other mounting systems can be used.

## TECHNICAL SPECIFICATIONS

height in mm	315	width in mm	175
depth in mm	195	loudspeaker system	2-way
woofer size in inch	6,5	woofer cone material	coated paper
tweeter size in inch	1	mounting system	intellimount
colour	black / white	100V transformer power taps in watts	60 - 30 - 15 - 6
impedance in ohms	16	low impedance dynamic power in watts	200
SPL 1W/1m in dB	90	max SPL 1m in dB	111
frequency response in Hz	65 - 20K	main construction material	ABS plastic
grille main material	aluminium	IP rating	64
applicable low impedance	Yes	applicable in 100V	Yes
Horizontal dispersion angle 1000 Hz	180°	Vertical dispersion angle 1000 Hz	180°
Net weight product (kg)	4,15		

[MORE PICTURES](#)



ACCESSORIES



**MASKW-BL**

Double V-shaped cluster bracket for MASK4(T)-BL/MASK6(T)-BL



**MASKV-BL**

V-shaped 2-way cluster bracket for MASK4(T)-BL / MASK6(T)-BL



**MASKL-BL**

L-shaped side bracket for MASK4(T)-BL / MASK6(T)-BL